

Application Serial No. 10/051,065

**AMENDMENTS TO THE CLAIMS**

1. (Cancelled)
2. (Cancelled)
- 5 3. (Cancelled)
4. (Cancelled)
5. (Cancelled)
6. (Cancelled)
7. (Cancelled)
- 10 8. (Cancelled)
9. (Cancelled)
  
10. (Previously Presented) In a directory server containing heterogeneous directory entries and a directory views hierarchy, each view containing a filter  
15 describing said view, a method of searching said view in said directory views hierarchy with a given filter, comprising the steps of:
  - (a) collecting filters from said view and all ancestor views of said view to form a first sub-filter;  
rewriting said given filter using said first sub-filter to be a sub-tree search  
20 of the parent of the topmost view in said view hierarchy; and  
performing said sub-tree search with said rewritten filter;  
wherein each of said directory views belongs to a specific object class that contains a filter attribute, said filter attribute containing a filter that describes said directory views.
- 25 11. (Original) The method of Claim 10, wherein said directory entries do not need to be physically in any particular place.

Application Serial No. 10/051,065

12. (Original) The method of Claim 10, wherein said directory server has a flat directory information tree.
- 5 13. (Original) The method of Claim 10, wherein the existence of said views is transparent to a client of said directory server and said client requires no special knowledge of said views to use them.
- 10 14. (Original) The method of Claim 10, wherein each of said directory views begins with an ordinary entry.
15. (Cancelled)
- 15 16. (Original) The method of Claim 10, wherein said filter attribute is omitted from said directory views to facilitate a hierarchical directory structure.
17. (Original) The method of Claim 10, wherein each of said directory views comprises sub-views which provide a subset of said views.
- 20 18. (Original) The method of Claim 17, wherein said sub-views comprise different subject domains from said directory views.
19. (Previously Presented) The method of Claim 10, said rewriting step comprising:
- 25 (b) if the search is not a sub-tree search, collecting all filters from all descendent views to form a second sub-filter;

Application Serial No. 10/051,065

(c) adding a third sub-filter to ensure all children of said view are included in the search for one level search or ensure all descendents of said view are included for a sub-tree search; and

5 (d) combining said first sub-filter, said second sub-filter, and said third sub-filter and said given filter to produce said rewritten filter.

20. (Previously Presented) The method of Claim 19, wherein step (a) further comprises the steps of:

- (1) starting from the topmost view and working down;
- 10 (2) adding each filter to said first sub-filter in step (a) using the logical AND operator; and
- (3) moving down said hierarchy and going to step (2) until at said view.

21. (Previously Presented) The method of Claim 19, wherein step (b) further  
15 comprises the steps of:

- (1) working down said hierarchy until said hierarchy ends;
- (2) adding each filter to said second sub-filter in step (b) using the logical AND operator and the logical NOT operator;
- (3) repeating step (2) until all sub-views of said view have been  
20 accounted for.

22. (Previously Presented) The method of Claim 19, wherein step (c) further comprises the steps of:

- (1) for sub-tree searches, using the logical OR operator and a filter which  
25 includes the components of said descendent views' distinctive attributes, and which excludes the distinctive attribute of said view;

Application Serial No. 10/051,065

(2) for one level searches, using the logical OR operator and a filter which includes the components of said children views' distinctive attributes, and which excludes the relative distinctive attribute of all children views of said view using the logical NOT operator; and

5 (3) for base searches, using the filter "objectclass=nsview", wherein "nsview" is the object class of said views.

23. (Previously Presented) The method of Claim 19, wherein step (d) further comprises the steps of:

10 (1) combining said third sub-filter from step (c) with the given search filter using the logical AND operator;

(2) combining said first sub-filter from step (a) and said second sub-filter from step (b) with the given search filter using the logical AND operator; and

15 (3) combining the resulting filters from step (1) and (2) using the logical operator OR.

24. (Original) The method of Claim 19, wherein said sub-filters from steps (a), (b) and (c) may be cached so that the filter rewriting only needs to perform step (d), which amounts to simple filter concatenation.

20

25. (Previously Presented) A directory server for managing heterogeneous directory information, comprising:

a plurality of directory entries;

a flat directory information tree;

25 a set of directory views to facilitate hierarchical navigation of said directory entries; and

means to search said directory views by rewriting filters.

Application Serial No. 10/051,065

26. (Original) The directory server of Claim 25, wherein said directory entries do not need to be physically in any particular place.

5 27. (Cancelled)

28. (Cancelled)

10 29. (Original) The directory server of Claim 25, wherein the existence of said directory views is transparent to a client of said directory server and said client is not required to have special knowledge of said directory views to use them.

30. (Original) The directory server of Claim 25, wherein each of said directory views begins with an ordinary entry.

15

31. (Original) The directory server of Claim 25, wherein each of said directory views belongs to a specific object class that contains a filter attribute, said filter attribute containing a filter that describes said directory views.

20 32. (Original) The directory server of Claim 25, wherein said filter attribute is omitted from said views to facilitate a hierarchical directory structure.

33. (Original) The directory server of Claim 25, wherein each of said directory views comprises sub-views that provide a subset of said directory views.

25

Application Serial No. 10/051,065

34. (Original) The directory server of Claim 33, wherein said sub-views comprise different subject domains from said directory views.

35. (Currently Amended) ~~The method of Claim 1, wherein said step of~~  
5 ~~organizing further comprises the step of:~~ In a directory server containing  
heterogeneous directory entries, a method of hierarchically navigating said  
entries comprising the steps of:  
creating one or more directory views;  
organizing said directory views into a hierarchy, wherein said step of  
10 organizing uses only information concerning said entries, wherein each of said  
directory views belongs to a specific object class that contains a filter attribute,  
said filter attribute containing a filter that describes said directory view;  
collecting filters from said directory views and all ancestor views of said  
directory views to form a first sub-filter; and  
15 using one of said directory views that is most appropriate for navigating to  
said entries.

36. (Original) The method of Claim 35, said organizing step further comprising the steps of:

20 using said first sub-filter to be a sub-tree search of the parent of the  
topmost view in said view hierarchy

if the search is not a sub-tree search, collecting all filters from all  
descendent views to form a second sub-filter;

25 adding a third sub-filter to ensure all children of said view are included in  
the search for one level search or ensure all descendents of said view are  
included for a sub-tree search; and

combining said first sub-filter, said second sub-filter, and said third sub-  
filter to produce a rewritten filter.

Application Serial No. 10/051,065

37. (Currently Amended) ~~The method of Claim 1, wherein said step of organizing further comprises the step of:~~ In a directory server containing heterogeneous directory entries, a method of hierarchically navigating said entries comprising the steps of:

- 5        creating one or more directory views;
- organizing said directory views into a hierarchy, wherein said step of organizing uses only information concerning said entries, wherein each of said directory views belongs to a specific object class that contains a filter attribute, said filter attribute containing a filter that describes said directory view;
- 10        rewriting said filter attribute using a first sub-filter; and
- using one of said directory views that is most appropriate for navigating to said entries.

38. (Currently Amended) The method of Claim 35[1], further comprising
- 15        means to search said directory views by rewriting filters.